

PATENT  
450117-03255

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

TITLE: METHOD FOR CONTROLLING NETWORK DEVICES  
VIA A MMI

INVENTORS: Arnd KRUSCHE, Stuart ALLEN

William S. Frommer  
Registration No. 25,506  
FROMMER LAWRENCE & HAUG LLP  
745 Fifth Avenue  
New York, New York 10151  
Tel. (212) 588-0800

0990125.070901

# Descripti n

- 1 The present invention generally relates to a method for controlling network de-  
vices via a MMI by which an easy and fast control of various kinds of devices is  
provided for a user. In addition, the present invention relates to a MMI for con-  
trolling said network devices, and to a computer program adapted to execute  
5 said method.

Generally, a network, such as a home network, comprises several devices.  
Such a device may be a controller to control other devices, or a target device, i.  
e. a controllable device which is controlled by a controller. As for example, a  
10 home network may comprise all various kinds of devices such as PC-, AV-,  
Telematics- and Communication-devices which are typically present in a home,  
e. g. in different places like first floor, second floor, distinct rooms etc.. Due to  
the large variety of different devices it is an important aspect for said network  
that efficient data lines are provided by which large quantities of data and/or  
15 different kinds of data may be exchanged. Nowadays, an appropriate data  
transmission between the devices connected to such a network is advanta-  
geously realized on the basis of the IEEE 1394 standard which is a powerful  
technology that meets many of the requirements of home networks.

- 20 Since their widely-spread distribution due to falling prices and enhanced chip  
capabilities Personal Computers have become an integral part of the home  
network philosophy. Usually, Personal Computers are used in home networks  
as controllers in order to provide an easy control of other devices, e. g. by  
means of a common user interface.

25

Fig. 6 shows an example for a possible network configuration according to the  
prior art wherein a home network representing a typical structure of a home is  
constituted of a plurality of devices arranged in sub-networks. Said home net-  
work comprises e.g. a first sub-network 1 named "Home Floor 1" which is lo-  
30 cated on the first floor of the home, a second sub-network 2 named "Home  
Floor 2" which is located on the second floor of the home, a third sub-network  
3 named "IP Network", a fourth sub-network 4 named "Car" which is located  
within a car, a fifth sub-network 5 named "Friend" which is located in the  
home of a friend, and a sixth sub-network 6 named "any other network" which  
35 is located anywhere else outside the home.

1 As shown in Fig.6, the first sub-network 1 comprises various electronic devices  
such as a PC 101, an Audio/Video Hard Disc (AVHD) 102, a TV 103, a Camcor-  
der 104, a Memory Stick Walkman 105 and a Data Video Home System (DVHS)  
106. Data transmission within the first sub-network 1 is based on the IEEE  
5 1394 standard. For example, the PC 101 may be used as controller within the  
first sub-network 1, e. g. to record files from the AVHD 102 to the Memory  
Stick Walkman 105.

10 The second sub-network 2 comprises an Amplifier 107, a Digital Audio Broad-  
casting (DAB)-Tuner 108, a Camcorder 109, a Projector 110 and a Home Appli-  
ances Control System 132. In this second sub-network 2, the data  
transmission is also based on the IEEE 1394 standard. The Home Appliances  
Control System 132 behaves as a controller for numerous devices. For exam-  
15 ples, the devices 107-110 connected to the second sub-network 2 may be con-  
trolled by the Home Appliances Control System 132.

20 Further, the second sub-network 2 is connected to the first sub-network 1 via  
a second bridge 129 which enables a data exchange between the first sub-net-  
work 1 and the second sub-network 2. In the illustration of Fig. 6, the second  
bridge 129 is connected to the first sub-network 1 and the second sub-network  
2 and is not included within one of said first or second sub-networks 1 or 2.  
This signifies that the second bridge 129 does not perform a protocol conver-  
sion during a data exchange, because both first and second sub-networks 1  
and 2 are based on the same standard, namely IEEE 1394. In case of a data  
25 transmission via the second bridge 129 it is possible to control the devices  
107-110 connected to the second sub-network 2 not only via the Home Appli-  
ances Control System 132, but also via the PC 101 connected to the first sub-  
network 1. It is further possible to control the devices 101-106 connected to  
the first sub-network 1 via the Home Appliances Control System 132.

30 With reference to the first sub-network 1 and the second sub-network 2, the  
devices connected thereto may preferably use the Audio Video Command (AV/  
C)-protocol in accordance with their generic type. Alternatively, said devices  
may also use another appropriate protocol standard.

35 The third sub-network 3 shown in Fig. 6 comprises electronic devices such as  
a Portable Phone 111, a Personal Digital Assistant (PDA) 112 and a Laptop

1 113. For example, the PDA 112 may be a handheld computer. Said devices  
111-113, contrary to the devices connected to the first and second sub-net-  
works 1 and 2, may not use the AV/C-protocol, but rather the internet proto-  
col.

5

The fourth sub-network 4 comprises electronic devices such as an Amplifier  
114, a Navigation Unit 115, a Tuner 116, a CD-Changer 117, a MD-Changer  
118, a Display 119 and a Portable Phone 120. Further, the fifth sub-network 5  
comprises electronic devices such as a Camcorder 121, an Audio/Video Hard  
10 Disc (AVHD) 122, a Still Picture Camera 123, a TV 124, a Set-Top-Box 125 and  
a DVHS 126. Both the fourth sub-network 4 and the fifth sub-network 5 are  
based on the IEEE 1394 standard.

The third sub-network 3 is connected to the first sub-networks 1, the fourth  
15 sub-network 4 and the fifth sub-network 5 via a first bridge 128, a third bridge  
130 which is a remote bridge, and a fourth bridge 131, respectively. Thus, data  
transmission is possible between the respective sub-networks. Due to different  
protocol standards of the first sub-network 1, the fourth sub-network 4 and  
and the fifth sub-network 5 on the one hand, and the third sub-network 3 on  
20 the other hand, a protocol conversion has to be executed in case of a data ex-  
change between the third sub-network 3 and one of the first, fourth or fifth  
sub-networks 1, 4 or 5. With respect thereto, unlike the second bridge 129,  
said first, third and fourth bridges 128, 130 and 131 are included within the  
corresponding sub-networks so that no further connection thereto is neces-  
25 sary, respectively. This signifies that said first, third and fourth bridges 128,  
130 and 131 handle said protocol conversion, wherein AV/C frames are trans-  
mitted inside IP frames, and vice versa.

If data is transmitted from the first sub-network 1 to the fifth sub-network 5  
30 via the third sub-network 3, the latter is used as a transparent transport me-  
dium. This allows the first and fifth sub-networks 1 and 5, which are based on  
the IEEE 1394 standard, to be connected via a non IEEE 1394 sub-network as  
if they were connected like two IEEE 1394 sub-networks, e. g. the first sub-  
network 1 and the second sub-network 2. Through the provision of said first to  
35 fourth bridges 128-131 the electronic devices connected to the fourth or fifth  
sub-networks 4 or 5 are accessible from the first or second sub-networks 1 or  
2, for example.

- 1 In addition, it is obvious that said home network may be extended by any  
other discrete sixth sub-network 6 comprising any other device 127. Further-  
more, any number of devices connected to a sub-network are controllable by a  
control system which is connected to the home network via the same sub-net-  
5 work or a distinct sub-network.

Document WO 95/59282 A2 discloses a method and a system for controlling  
diverse home devices which are all connected to a network, e. g. a home net-  
work. The teaching of said document explicitly excludes Personal Computers  
10 being a part of said network. Control and command information is sent from a  
control device to a target device in order to control the target device according  
to an user input. Since the control device can display an user interface trans-  
mitted thereto from any target device connected to the network, a single  
control device may control a plurality of different target devices without requir-  
15 ing any change in the mode of operation of the control device.

According to the teaching of said document, communication on the home net-  
work is basically provided through the use of the TCP/IP-standard network  
protocols. Each target device connected to said network is discovered. Subse-  
quently, a device link page is loaded which contains home device buttons for -  
20 each home device connected to the home network.

Therefore, if the user wants to get access to services of a specific home device,  
a session manager generates an interface displaying a loaded top level home  
25 page of the respective home device with reference to said home device buttons.

Further, it is to be noted that each top-level home page for a respective home  
device has a different structure according to different operating functions as-  
sociated therewith. Hence, the user has to concentrate on different structures  
30 of distinct top-level home pages, respectively.

Therefore, it is the object of the present invention to provide a method for con-  
trolling various kinds of devices connected to a network via a Man Machine In-  
terface (MMI), by which an easy control is possible for the user.

35

This object is achieved by a method for controlling network devices via a MMI  
according to claim 1. Preferred embodiments are defined in dependent claims 2  
to 9.

- 1 The method according to the invention comprises the following steps: generat-  
ing and at least partially displaying a hierarchical view of icons of all devices  
connected to the network and/or services corresponding to the devices, and  
coupling each of said icons with operating functions of the associated device  
5 and/or service, respectively, wherein said devices and/or services are  
operatable from said hierarchical view.

The method according to the invention is based on a tree-based control,  
wherein said network, preferably a home network, its devices and their serv-  
10 ices are preferably treated as an extension of an existing Personal Computer  
hierarchical file system which has been formerly known only for file manage-  
ment on a PC. According to the invention it is possible to control all devices  
and/or services corresponding to the devices in the same way, irrespective of  
their type and their local connection to said home network. Since the structure  
15 of said known hierarchical file system is similar to the view of icons generated  
according to the invention, the user can directly control all devices and/or  
services corresponding thereto, which are included within said home network,  
from one common MMI in a familiar and comprehensive manner. This ap-  
proach provides a very easy and fast control for the user, because the opera-  
20 tion mode thereof is self-explaining.

The method according to the invention supports not only non-computer de-  
vices like audio/video or communication devices and their services, but also  
computer storage devices (organized e.g. by folders and files). By means of this  
25 approach, it is possible to make use of all the functionality currently available  
from known browser systems. In this context, browser is used as a generic  
name, wherein the meaning thereof is not limited only to a HTML browser such  
as Microsoft Explorer® or Netscape Navigator®. Nevertheless, it is to be und-  
erstood that the present invention is not exclusively browser-based, but rather  
30 related to a tree-like hierarchical structure in general.

Preferably, a sub-network being integrated in said home network is recognized  
via a bridge and integrated as an icon in said hierarchical view of icons similar  
to said devices and/or services, wherein said icon assigned to said sub-  
35 network has a higher order than icons assigned to devices and/or services of  
said sub-network. Hence, other networks that are connected to the local home  
network are included in this hierarchy. These sub-networks are made a logical  
part of the home network through the use of the aforementioned bridge de-

1 vices, and thus a part of the hierarchy. The other sub-networks may be based upon the same or different protocols, and the same or different physical layer.

Further preferably, a device and/or service is operatable by drag and drop operations, e. g. for copying audio streams to a storage device like a memory stick. Alternatively, a device and/or service may also be operatable by cut/copy and paste operations. As for consequence, the user is enabled to execute any control of a device and/or service directly from said view of icons, which leads to a very easy and fast operation mode. The user is not required to take  
10 any preparatory steps before executing said control operations.

Still further preferably, a device and/or service is operatable via context sensitive menus shown in said hierarchical view after selecting the icon associated with said device and/or service. As for example, the user can operate the device and/or the service corresponding thereto by using the right mouse button menu. In the same way as "right clicking" on a hard disk which allows to format and share the disk, the user may "right-click" on a DAB-receiver connected to the home network which would allow him to tune it up, find its properties, share it with other network users etc., even to users who  
15 may be outside the "own" network. For a more comprehensive control, specific applications may be associated to resources. These applications would launch when the appropriate action is taken, or situation arises. For example, an AV editing suite could be associated with audio and video files, and a DAB control panel for a DAB receiver.  
20

25 Still further preferably, after operation at least one control signal and/or at least one data stream is sent from one device to at least one other device. By using of this kind of MMI-viewer/manager, the user does not need to be aware of the physical storage or transmission media, since only the access and processing of a respective object is of importance for the user.  
30

Still further preferably, said hierarchical view of icons is organized according to predetermined user-selectable rules. In this way, it is possible for the user to organize said hierarchical view of icons according to respective control operations. Further, the user can advantageously adapt said hierarchical view of icons to frequent control steps being typical of his habits.  
35

Still further preferably, or alternatively, said hierarchical view of icons is

- 1 organized depending on the kind of said devices and/or sub-networks connected to the home network.

5 In this case, said hierarchical view of icons may comprise a properties dialog accessible through a context sensitive menu as explained above. Said properties dialog would be a small information dialog that may include basic controls such that the user is allowed to control certain parameters of a respective device. As for example, if a heating system is included within the home network, the properties dialog may include a basic control such as a timer combined  
10 with heating controls. Correspondingly, the information displayed within said small information dialog could be current ambient/water temperature. In another example the properties dialog could include information such as station frequency, station name and signal quality for a tuner unit included within the home network. In the example of a video recorder included within the home  
15 network the properties dialog could include information such as tape length, remaining play time or the like.

Still further preferably, or alternatively, said hierarchical view of icons is organized depending on the kind of services being available in correspondence with  
20 said devices. By means of this object-oriented view, all multimedia object types (audio-, video-, data-files, streams, services etc.) being available on the home network and all possible processing services (copying, storing, mixing, filtering, rendering, sending) corresponding to the devices can be identified and displayed, wherein said processing services can be accessed via said display.

25

As for example, the user is allowed to simply select a live audio stream on a DAB receiver and drag it to a memory stick walkman, both included within the home network. This would record the audio stream onto the walkman in a very simple way. As another example, an output of a security camera could be received by simply finding it within said hierarchical view of icons. A stream associated thereto could be displayed in real-time on-screen. This approach could  
30 be extended to a very effective video conferencing system or a nursery monitoring.

35 Still further preferably, the AV/C protocol is used for controlling the devices and/or services. Nevertheless, it is to be understood that within the home network, any other appropriate kind of protocol, such as the TCP-, IP- or FCP-protocol, may be used in order to support a device different from audio/video,



1 such as printers, copy machines or the like.

Further, it is an object underlying the present invention to provide an interface device by which an easy and comprehensive control for the user is rendered  
5 possible.

This object is solved by a MMI for controlling network devices according to claim 10, wherein said MMI is based on a known hierarchical file navigation concept and adapted to perform the method as defined in any one of claims 1  
10 to 9.

A further object underlying the present invention is to provide a computer program product by which an easy and comprehensive control for the user is rendered possible.

This object is achieved by a computer program product according to claim 11, wherein said computer program product comprises a computer program means which is based on a known hierarchical file navigation concept and adapted to execute all steps defined in any one of claims 1 to 9, when said computer program product is executed on a computer.  
20

Further objects, features and advantages of the present invention will be better understood from the following detailed description of advantageous embodiments thereof taken in conjunction with the accompanying drawings, wherein:  
25

**Fig. 1** illustrates an example of a browser based MMI according to the present invention wherein a hierarchical view of icons generated according to the present invention is organized depending on the kind of devices and/or sub-networks included within a home network;  
30

**Fig. 2** illustrates an example of a browser based MMI according to the present invention wherein a hierarchical view of icons generated according to the present invention is organized depending on the kind of services being available corresponding to said devices;  
35

**Figs. 3a,3b** illustrate an example of a network communication according to the present invention wherein a file transfer from a PC to a

1 navigation unit is executed;

**Figs. 4a,4b** illustrate another example of a network communication according to the present invention wherein a DV stream from a DVHS is copied to an AVHD via a control by a PC;

**Figs. 5a,5b** illustrate still another example of a network communication according to the present invention wherein a DAB audio stream from a DAB tuner is copied to a memory stick walkman via a control by a PC, and

**Fig.6** shows a configuration of a known network including various kinds of devices and several sub-networks.

15 Fig. 1 illustrates an example of a browser-based MMI according to the present invention wherein a hierarchical view of icons generated according to the present invention is organized depending on the kind of devices and/or sub-networks included within a network, preferably a home network. Fig. 1 shows a main window 7 of the MMI positioned on the left side, in which icons assigned to sub-networks, devices and services available on the home network are displayed. Said hierarchical view according to the present invention is similar to a view e.g. shown in a browser window of the Microsoft Explorer®, but it is of course not limited thereto.

25 In its highest order, said hierarchical view comprises icons which are assigned to a traditional computer file system 9 which is named "My Computer", a seventh sub-network 15 named "Network Neighborhood", an eighth sub-network 21 which is named "My AV-Network" and a ninth sub-network 36 which is named "My Communication-Network". Said traditional computer file system 9 and said seventh to ninth sub-networks 15, 21 and 36 are all part of the home network and are all viewed in the same hierarchical manner, in conjunction with respective devices and/or services available within a respective sub-network which is further explained below. In said example each sub-network is treated as an extension of an existing file system which can be found on Personal  
35 Computers.

Further in detail, the icon assigned to "My Computer" 9 is superordinated to icons which are assigned to different drives of said computer, i. e. Floppy (A:)

1 10, System (C:) 11, Program (D:) 12, Data (E:) 13 and Disc (F:) 14, respectively.  
Further, the drive System 11 comprises directories OS 11a and Temp 11b,  
wherein icons assigned thereto are subordinated to the icon assigned to said  
drive System 11. Still further, the directory Temp 11b comprises a sub-directory  
5 Private 11c, wherein an icon assigned thereto is subordinated to the icon as-  
signed to said directory Temp 11b.

The icon assigned to the seventh sub-network 15 is superordinated to further  
icons which are assigned to a PC A 17, a PC B 18, a Server A 19 and a Server B  
10 20, which are included within said seventh sub-network 15. Further, an icon  
assigned to the Entire Network 16 of the seventh sub-network 15 is subordi-  
nated to the icon assigned to said seventh sub-network 15. It is to be under-  
stood that the icon assigned to the Entire Network 16 defines a purely organisa-  
tional tool which is configurable by the user. This tool allows to generate a dis-  
15 play of simply all icons assigned to any device included within the seventh sub-  
network 15 regardless of the respective physical connection and hierarchical or-  
der therein.

The icon assigned to the eighth sub-network 21 is superordinated to icons which  
20 are assigned to a MD-Changer 23, a CD-Changer 24, a DVD-Player 25, a DAB-  
Receiver 26, a DVB-Receiver 27, an AV-HD 28, a Memory Stick Drive 29, a Dis-  
play 30 and a Camcorder 31, which are included within the eighth sub-network  
21. Further, Fig. 1 shows that as for example, three different CD titles 24a-24c  
are available from different compact disks available in the CD-Changer 24. For  
25 this reason, three icons assigned to a CD-Title A (CD1) 24a, a CD-Title B (CD 2)  
24b and a CD-Title C (CD 2) 24c, respectively, are subordinated to the icon  
which is assigned to the CD-Changer 24.

Still further, in said example two radio stations DAB Stuttgart 42 and BBC Na-  
30 tional 43 are available from said DAB receiver 26. Correspondingly, two icons  
assigned to DAB Stuttgart 42 and BBC National 43, respectively, are subordi-  
nated to the icon assigned to the DAB receiver 26.

Still further, in said example a plurality of radio programs is broadcast by the  
35 radio station BBC National 43, i. e. BBC World Service 43a, BBC R1 Digita 43b,  
BBC Xtra 43c, BBC 5Live Sport+ 43d, Heart 43e, Sunrise 43f and BBC Air Web  
43g. Accordingly, icons assigned to these radio programs 43a-43g are subordi-  
nated to the icon assigned to the radio station BBC National 43. In this context,

1 it is to be noted that said icons assigned to the radio programs 43a-43g may symbolize directories in which streams corresponding to further services may be stored.

5 Still further, the Camcorder 31 comprises a Camera 32, a Display 33, a Tape Recorder 34 and a Memory Stick Drive 35. Accordingly, icons assigned to the devices 32-35 are subordinated to the icon which is assigned to the Camcorder 31.

10 In addition, the icon assigned to the eighth sub-network 21 "My AV-Network" is superordinated to an icon assigned to the Entire AV-Network 22 which defines a purely organisational tool that can be configured by the user. As explained above for the icon assigned to the Entire Network 16, this tool allows to generate a display of simply all icons assigned to any device included within the eighth sub-network 21 "My AV-Network" regardless of either a possible subordi-  
15 nation to an icon of a device having a higher order or a subordination to an icon assigned to a workgroup (not shown) of devices, which could be a workgroup of all Audio Devices or all Video Devices, for example.

20 The icon assigned to the ninth sub-network 36 is superordinated to icons which are assigned to an ISDN-Phone 38, a Mobile Phone 39, a Pager 40 and a Video Conferencing System 41, which are included within the ninth sub-network 36. Further, the icon assigned to the ninth sub-network 36 is superordinated to an icon assigned to the Entire Communication Network 37. Like the icons assigned to the Entire Network 16 and the Entire AV-Network 21, the icon assigned to the  
25 Entire Communication Network 37 defines a purely organisational tool which is configurable by the user. This tool allows to generate a display of simply all icons assigned to any device included within the ninth sub-network 36 regardless of a possible subordination to an icon of a device having a higher order with respect to the respective physical connection.

30

Fig. 1 further shows an additional window 8 positioned on the right hand side next to the main window 7, in which further information can be displayed for the user. This information include available components/streams and/or services, in accordance with a device and/or service displayed in the main win-  
35 dow 7, which has been selected by the user. As for example, the radio program BBC Xtra 43c offers services like BBC Xtra Audio 44 and BBC Xtra Traffic Data 45. If the user selects said radio program BBC Xtra 43c displayed in the main

1 window 7, in order to execute further control operations, said services BBC Xtra  
Audio 44 and BBC Xtra Traffic Data 45 are displayed within said additional win-  
dow 8.

5 Alternatively, or additionally, it is possible to display further available devices  
and/or services via a first context sensitive menu 46, which might be displayed  
simultaneously with said main window 7 and said additional window 8. The  
context sensitive menu 46a can be activated by clicking e. g. the right mouse  
button. By means of said first context sensitive menu 46, as for example, the  
10 user gets access to functional services, such as Explore 46a, Open 46b, Find  
46c, Copy 46d, Sharing 46e, Map Network Device 46f, Rewind 46g, Play 46h,  
Fast Forward 46i, Pause 46j, Stop 46k, Create Shortcut 46l, Delete 46m, Re-  
name 46n and Properties 46o. Of course, any other service and/or device can be  
displayed in said first context sensitive menu 46. Still further, it is to be under-  
15 stood that either one context sensitive menu or a plurality of context sensitive  
menus can be activated with regard to a device and/or a service shown in the  
main window 7 and/or the additional window 8.

From the display explained above and shown in Fig. 1, it is clear that the user is  
20 supplied with a complete overview of all available sub-networks, and further of  
all devices connected to the distinct sub-networks and/or services  
corresponding to the devices. A respective number of icons is generated  
according to the present invention, which is representative for all sub-networks,  
devices and/or services included within the home network.

25 As to explain the function of controlling said devices and/or services included  
within said home network according to the invention, reference is now made to  
the eighth sub-network 21 "My AV-Network. As mentioned above, the radio  
program BBC Xtra 43c is broadcast by the radio station BBC National 43  
30 available from the DAB Receiver 26 which is included within the eighth sub-net-  
work 21. In said example, the user selects the radio station BBC Xtra 43c so as  
to execute further control operations with respect thereto. As for consequence,  
the symbol of "BBC Xtra" 43c is highlighted, and the services corresponding  
thereto, i. e. BBC Xtra Audio 44 and BBC Xtra Traffic Data 45, are displayed  
35 within the additional window 8. Based on this display mode, the user is now  
enabled to drag e. g. BBC Xtra Audio 44 and drop it e. g. on the icon assigned to  
the Memory Stick Drive 29. By means of this drag and drop operation, the user

1 can easily record the audio program of BBC Xtra 43c on the Memory Stick Drive  
29. Subsequently to this operation, a data stream is generated according to the  
invention, which is sent from the DAB Receiver 26 to the Memory Stick Drive  
29.

5

In the same way, the user might drop e.g. BBC Xtra Traffic Data 45 and drop it  
to any icon assigned to a device included within the eighth sub-network 21  
which would be responsive to this kind of service. Of course, the control of said  
services 44 and 45 is not limited to the examples given above, and can also be  
10 executed with any suitable device included within a sub-network different from  
the eighth sub-network 21.

Alternatively, or additionally, controlling of said devices and/or services may  
also be executed via said first context sensitive menu 46. In order to explain the  
15 functioning thereof by way of example, reference is now made to the Tape Re-  
corder 34 which is included within the Camcorder 31. If the user selects the  
Tape Recorder 34 shown in the main window 7 in order to execute further  
control operations therewith, the symbol of "Tape Recorder" 34 is highlighted.  
Subsequently, said first context sensitive menu 46 can be activated by clicking  
20 e. g. the right mouse button, which displays further services associated with the  
Tape Recorder 34. Alternatively the selection of a device and/or service and the  
activation of the corresponding context sensitive menu can be performed by one  
user action. As shown in Fig. 1, the first context sensitive menu first 46 is  
displayed simultaneously with said main window 7 and said additional window  
25 8. From the listing of services corresponding to the Tape Recorder 34, which is  
displayed in said first context sensitive menu 46, as mentioned above, the user  
may choose the service Play 46h associated with the Tape Recorder 34 simply by  
choosing the highlighted symbol "Play". As for consequence a recording stored  
on said Tape Recorder 34 of said Camcorder 31 is reproduced. In general, said  
30 listing only includes services which are operatable with respect to a device that  
has been selected by the user.

With respect to the foregoing, it is to be understood that the control of the Tape  
Recorder 34 is not limited to the examples given above. Of course, any other  
35 control operation of a device and/or service would be possible within the home  
network via said hierarchical view of icons. Further, said first context sensitive  
menu 46 can also be activated with reference to a device and/or service which is  
not displayed in said main window 7, but rather in said additional window 8.

1 Still further, any control operation can be executed not only by a drag/drop operation or via a context sensitive menu, but also by cut/copy and paste or other similar operations.

5 In general, it is obvious from the example explained in connection with Fig. 1 that numerous combinations for a communication of one device connected to a first sub-network to another device connected to the same sub-network or to a second sub-network are rendered possible. It is pointed out that during controlling of a device and/or a service corresponding thereto, the user has not  
10 to deal with generating control signals and the like. According to the invention, each of said icons is coupled with operating functions of the associated device and/or service corresponding thereto, respectively. In this context, it is to be understood that said operating functions may preferably be identical with said functional services 46a-46h as mentioned above, but they are not limited  
15 thereto. After the user has terminated the operation, a control signal and/or at least one data stream is automatically generated by the method according to the invention, which is sent from one device to at least one other device.

Further with respect to the hierarchical view as explained above and shown in  
20 Fig. 1, the eighth and ninth sub-networks 21 and 36 included within the home network may not necessarily be understood only as physical networks wherein several devices are grouped depending on their location, i.e. a specific room in a house or a connection within a home network, and are served e.g. by the same physical bus. Alternatively, the eighth and ninth sub-networks 21 and 36 can  
25 also be considered as logical networks in which various devices are grouped together in accordance with their category, not depending on their respective location within the home and/or the home network, respectively.

Fig. 2 illustrates an example of a browser-based MMI according to the present  
30 invention wherein a hierarchical view of icons generated according to the present invention is organized depending on the kind of services being available in correspondence with said corresponding devices. The view of icons shown in Fig. 2 basically provides the same information as the view of icons shown in Fig. 1, but the structure thereof is organized in a different way compared to the view  
35 of icons shown in Fig. 1.

Fig. 2 shows the main window 7 and the additional window 8, in which icons assigned to various services are displayed. Within the main window 7, in its

1 highest order, said hierarchical view comprises icons which are assigned to  
services such as Audio 47, Video 48 and Data 49. Said services 47-49 are all  
available within the home network and are all viewed in the same hierarchical  
manner, in conjunction with further services related thereto.

5

In detail, services Audio Files 50 and Audio Streams 54 are subordinated to the  
service Audio 47. As for consequence, the icon assigned to Audio 47 is superor-  
dinated to icons assigned to Audio Files 50 and Audio Streams 54, respectively.  
In conjunction with the service Audio Files 50, different directories are provided  
10 in which files having an extension such as MPEG 51, Atrac 51 and .wav 53 can  
be stored, respectively. In accordance therewith, the icon assigned to the service  
Audio Files 50 is superordinated to icons assigned to MPEG 51, Atrac 51 and  
.wav 53.

15 The service Audio Streams 54 is superordinated to streams based on different  
languages such as English, German, French, Japanese. The service Audio S-  
streams 54 is also superordinated to a stream including information of a Phone  
talk which has been conducted e. g. to Mr. Gates. According thereto the icon as-  
signed to Audio Streams 54 is superordinated to various directories which are  
20 assigned to the streams of the different languages. As for consequence, icons  
assigned to English 55, German 56, French 57, Japanese 58 and Phone Talk  
(Mr. Gates) 59, respectively, are subordinated to the icon assigned to Audio  
Streams 54. Further, the English streams 55 include different radio programs,  
such as BBC Worldwide Service 43a, BBC R1 Digital 43b, BBC Xtra 43c, BBC  
25 5Live Sport+ 43d, Heart 21e and Sunrise 43f. Correspondingly, icons assigned  
to said radio programs 43a-43f are related to the icon assigned to English 55,  
wherein said icons may symbolize directories, respectively.

With reference to the service Video 48, video files and video streams are subordi-  
30 nated. Correspondingly, the icon assigned to Video 48 is superordinated to icons  
which are assigned to services Video Files 60 and Video Streams 63. According  
to different types of files which are available as video files, i. e. MPEG 61 and  
DV 62, different directories are subordinated to Video Files 60. According  
thereto, icons assigned to MPEG 61 and DV 62 are subordinated to the icon as-  
35 signed to Video Files 60. Further, video streams are available in English and  
German. In addition, a video stream is available including data about video  
conferencing, e. g. with Mr. Gates. Accordingly, icons assigned to English 64,  
German 65 and Video Conferencing (Mr. Gates) 66, respectively, are subordi-



1 nated to the icon which is assigned to Video Streams 63.

Said hierarchical view further provides information about data which is available e. g. in documents or via data services. Accordingly, the icon assigned to Data  
5 49 is superordinated to icons which are assigned to Documents 67 and Data Services 68, respectively. It is to be understood that said icons assigned to Documents 67 and Data Services 68, respectively, may symbolize directories. Still further, data is available from different data services, such as EPG, e-Commerce, e-Mail, Weather, the radio program BBC Air Web and the radio program  
10 service BBC Xtra Traffic Data. In correspondence thereto, the icon assigned to Data services 68 is superordinated to icons assigned to EPG 69, e-Commerce 70, e-Mail 71, Weather 72, BBC Air Web 73 and BBC Xtra Traffic Data 74, respectively, which may symbolize directories in which further files can be stored.

15 The additional window 8 displays further information for the user. This information includes available components/streams and/or services, in accordance with a device and/or service displayed in the main window 7. In said example, based on the selection of the radio program BBC Xtra 43c of the category English Audio Streams 55, the additional window 8 displays the radio program service  
20 BBC Xtra Audio 44. In correspondence with said service BBC Xtra Audio 44, a second context sensitive menu 75 is displayed simultaneously with said main window 7 and said additional window 8, wherein processing services are indicated, such as Open 75a, Send To 75b, Cut 75c, Copy 75d, Create Shortcut 75e, Delete 75f, Rename 75g and Properties 75h. Of course, any other service  
25 could be displayed in said second context sensitive menu 75.

Corresponding to the selection of the processing service Send To 75b, a third context sensitive menu 76 is displayed on the right hand side next to said second context sensitive menu 75. Within the third context sensitive menu 76, a  
30 selection of devices included within the home network is displayed, such as 3.5 Floppy 76a, Desktop 76b, Mail Recipient 76c, My Briefcase 76d, Amplifier 76e, AVHD 76f, TV 76g, Memory Stick Walkman 76h, Camcorder 76i and Video Telephone 76j. Alternatively any other context sensitive menu, or a plurality of context sensitive menus, can also be activated corresponding to a service which is  
35 displayed in said main window 7 and/or in said additional window 8. In this context, with reference to the kind of hierarchical view shown in Fig. 2, it is generally to be understood that only such functional services and devices are displayed in said context sensitive menus, which may be operatable in conjunc-

0990125-070901

tion with each other.

In the following, reference is made to the radio program BBC Xtra 43c in order to explain the control of the services shown in said hierarchical view of Fig. 2. In

case that the user selects BBC Xtra 43c in order to execute a control operation therewith the symbol of "BBC Xtra" 43c is highlighted and subsequently the

audio stream BBC Xtra Audio 44 which is provided by the radio program BBC Xtra 43c is displayed in the additional window 8, as described above. In order to

get access to processing services associated with BBC Xtra Audio 44 the user

can activate said second context sensitive menu 75 by clicking e. g. the right mouse button. Among the selection of services displayed in said second context

sensitive menu 75 the user can choose the service Send To 75b e. g. by mouse clicking or keyboard control. Subsequently to this operation the third context

sensitive menu 76 is activated in which a selection of devices corresponding to

said services displayed, as discussed above. Based on said selection of devices the user is now enabled to select e. g. the Memory Stick Walkman 76h from this

common MMI in order to send data of said radio program service BBC Xtra Audio 44 to the Memory Stick Walkman 76h. Subsequently to this operation a

data stream is generated according to the invention which is sent from the DAB

Receiver supplying the radio program service BBC Xtra Audio 44 to the Memory Stick Walkman 76h in order to perform said recording.

With respect to said hierarchical view shown in Fig. 2 it is to be understood that any other control can be executed with respect to any other service and/or

device included within the home network. Also, said control can not only be executed via a context sensitive menu, as in the example discussed above, but

also by a drag and drop operation and/or by cut/copy and paste or other similar operations.

By way of said example wherein data of BBC Xtra Audio 35 is sent to a Memory Stick Drive, it is clear that the same kind of data transmission can be executed

either via the hierarchical view organized depending on the kind of devices and/or sub-networks shown in Fig. 1, or via the hierarchical view organized

depending on the kind of services shown in Fig. 2.

In the following, examples for control operations executed within said home network are explained with reference to Figs. 3 to 5. In this context, the respective steps of data exchange between respective devices included within

1 said home network will also be explained.

In general, Figs. 3a, 4a and 5a illustrate an example of a network communication, respectively, which is basically constituted of the same devices and sub-networks connected via the same bridges as shown in Fig. 6, respectively. The same devices and sub-networks are designated with the same reference signs and named with the same expression, respectively, wherein a detailed explanation thereof is omitted. Contrary to Fig. 6, the Figs. 3a-5a only show devices which are relevant for the respective control operations. For reasons of simplicity, all other devices included within the home network are not shown in Figs. 3a-5a, since they are not relevant.

Figs. 3a and 3b illustrate an example of a network communication, wherein a file transfer from a PC to a navigation unit is executed. Contrary to Fig. 6, Fig. 3a only shows the devices which are relevant for the explained file transfer, i. e. the PC 101 which is connected to the first sub-network 1, and further the Navigation Unit 115 which is connected to the fourth sub-network 4. Further, Fig. 3a shows a plurality of arrows 3001, wherein an arrow 3001 is arranged between the PC 101 and the first bridge 128, further between the first bridge 128 and the third bridge 130 extending through the symbol of the third sub-network 3, and finally between the third bridge 130 and the Navigation Unit 115, respectively. The plurality of arrows 3001 defines a bidirectional data connection between the PC 101 and the Navigation Unit 115 which is used to control the Navigation Unit 115 and to send streams, and which is realized via the first sub-network 1, the first bridge 128, the third sub-network 3, the third remote bridge 130 and finally the fourth sub-network 4. In the following, such a data connection is only referred to "first data connection 3001".

In Fig. 3b, the respective steps required for said file transfer shown in Fig. 3a are explained. At first, in step S 301, the user selects the icon assigned to the fourth sub-network 4, by which an output signal to the PC 101 is generated. The PC 101 is provided with an explorer-based MMI, as shown for example in Fig. 1 and 2, respectively. Thereafter, in step S 302, the PC 101 outputs a remote wake-up signal to the Navigation Unit 115 via said first data connection 3001.

As a response to receiving the remote wake-up signal from the PC 101, in step S 303, the Navigation Unit 115 outputs a signal back to the PC 101 in order to announce being on the bus, also using said first data connection 3001. In this

- 1 step, also other devices connected to the fourth sub-network 4 "Car" might announce to be on the bus. Then, in step S 304, the display of the MMI indicates the new bus topology to the user, i.e. all devices and/or services being directly subordinated to "Car". Subsequently in step S 305, the user selects the newly
- 5 shown icon assigned to the Navigation Unit 115, which generates a corresponding signal within the PC 101. As for consequence, in step S 306, the PC 101 reads the status/property data from the Navigation Unit 115 via said first data connection 3001. Following this action, in step S 307, respective signals representing the status/property data of the Navigation Unit 115 are sent back
- 10 to the PC 101 via said first data connection 3001. In general, these signals provide information which is used internally e.g. in the PC or any other controller as a part of an appropriate control protocol in order to determine type and capabilities of a device when included within the home network.
- 15 Subsequently, in step S 308, the PC 101 reads the directory from the Navigation Unit 115 via said first data connection 3001, whereinafter in step S 309, the directory data are sent from the Navigation Unit 115 to the PC 101 via said first data connection 3001 and displayed within the MMI. By displaying said directory to the user, the user is allowed e.g. to view the map data which are already
- 20 installed or available on the Navigation Unit 115. However, this step may not be necessary for all types of navigation systems depending on the upgrade version of the system.

Subsequently, in step S 310, the user drags a local file, e.g. route data, and

25 drops it on the icon assigned to a directory of the Navigation Unit 115, which is displayed on the MMI provided within the PC 101. As for result, in step S 311, the PC 101 executes a set-up for the Navigation Unit 115 via first said data connection 3001 for receiving data and saving to a file. In the last step S 312, the PC 101 sends a file to the Navigation Unit 115 via said first data connection

30 3001, wherein said file transfer from the PC 101 to the Navigation Unit 115 is accomplished.

Figs. 4a and 4b illustrate another example of a network communication, wherein the user decides to copy a DV stream from DVHS 106 to AVHD 102. This

35 network communication is executed preferably on the basis of a hierarchical view of icons depending on the kind of devices and/or sub-networks, as shown in Fig. 1, but is not limited thereto.

1 In addition to the first to sixth sub-networks 1-6 and with respect to devices in-  
cluded within the home network, Fig. 4a only shows the PC 101, the AVHD 102  
and the DVHS 106, which are all connected to the first sub-network 1. Further,  
an arrow 1001 is shown which is arranged between the PC 101 and the DVHS  
5 106. This arrow 1001 defines a bidirectional asynchronous data connection  
between the PC 101 and the DVHS 106 which is used to control the DVHS 106  
and is realized via the first sub-network 1. In the following, such data connec-  
tion is only referred to "first control connection 1001".

10 Further, Fig. 4a shows an arrow 1002 which is arranged between the PC 101  
and the AVHD 102. This arrow defines a bidirectional asynchronous data con-  
nection between the PC 101 and the AVHD 102 which is used to control the  
AVHD 102 and is realized via the first sub-network 1. In the following, for such  
a data connection reference is only made to "second control connection 1002".

15 Still further, there is shown an arrow 1003 arranged between the DVHS 106 and  
the AVHD 102 which defines a unidirectional isochronous data connection. Data  
streams can be transferred via this type of data connection. In the following,  
reference is only made to "first transfer connection 1003" for such a data  
20 connection between the DVHD 106 and the AVHD 102 which is realized via the  
first sub-network 1. It is to be noticed that said first transfer connection 1003 is  
logically different from said first and second control connections 1001 and 1002.  
The first and second control connections 1001 and 1002 are bidirectional asyn-  
chronous transient connections which are used to negotiate or set up the unidi-  
25 rectional isochronous first transfer connection 1003.

With reference to Fig. 4b, the respective steps will be explained which are  
necessary for copying said DV stream from the DVHS 106 to the AVHD 102. Ini-  
tially, in step S 401, the user switches on the DVHS 106. Subsequently, in step  
30 S 402, the DVHS 106 announces to the PC 101 via said first control connection  
1001 to be on the bus. An explorer based MMI, as it is illustrated in Figs. 1 and  
2, for example, is provided within the PC 101 and presents the new bus topol-  
ogy including the DVHS 106 to the user in step S 403. Subsequently, the user  
switches on the AVHD 102 in step S 404, whereinafter in step S 405, the AVHD  
35 102 announces to the PC 101 via the second control connection 1002 to be on  
the bus. In the following, in step S 406, this change of the bus topology is  
indicated to the user via the MMI.

1 After both devices DVHS 106 and AVHD 102 are in an operating mode, the user  
selects the icon assigned to the AVHD 102 in step S 407. Subsequently, in step  
S 408, the PC 101 reads the directory of the AVHD 102 via said second control  
connection 1002. In return, in step S 409, information representing the  
5 directory data AVHD 102 is sent back to the PC 101 via said second control  
connection 1002. Thereafter, the present directory of the AVHD 102 is displayed  
to the user via the MMI according to the present invention in step S 410. In the  
next step S 411, the user selects on the icon assigned to the DVHS 106, which  
makes the PC 101 read a status/property data from the DVHS 106 via said first  
10 control connection 1001 in step 412. In return, in step S 413, a data stream  
representing the status/property data of the DVHS 106 is sent to the PC 101  
again via said first control connection 1001. After the PC 101 has received the  
respective information, in step S 414, the present stream of the DVHS 106 is  
displayed to the user via the MMI.

15 After the necessary information of the DVHS 106 and the AVHD 102 is  
displayed via the MMI, in step S 415, the user subsequently drags the DVHS  
video stream and drops it on the icon assigned to a directory of the AVHD 102,  
preferably based on the hierarchical view as illustrated in Fig. 1. After this  
20 operation, in step S 416, the PC 101 sends a signal via the second control con-  
nection 1002 in order to set up the AVHD 102 for receiving a DV stream and  
writing to a file. In step 417, the PC 101 also sends a signal via the first control  
connection 1001 to the DVHS 106 in order to set up this device for sending data  
to the AVHD 102. Finally, in step S 418, said DV stream is copied from the  
25 DVHS 106 to the AVHD 102 via the first transfer connection 1003 wherein the  
copying of said DV stream is accomplished.

Figs. 5a and 5b illustrate a further example of a network communication,  
wherein the user decides to copy a DAB audio stream from DAB-Tuner 108 to  
30 Memory Stick Walkman 105. This network communication is executed  
preferably on the basis of a hierarchical view of icons depending on the kind of  
services, as shown in Fig. 2, but is not limited thereto. Correspondingly, in ad-  
dition to the first to sixth sub-networks 1-6 Fig. 5a only shows the PC 101 and  
the Memory Stick Walkman 105 which are connected to the first sub-network  
35 1, and the DAB-Tuner 108 which is connected to the second sub-network 2.

Fig. 5a further shows an arrow 2001 which is arranged between the PC 101 and

1 the DAB-Tuner 108. This arrow 2001 defines a bidirectional data connection  
between the PC 101 and the DAB-Tuner 108 which is used to control the DAB-  
Tuner 108 and is realized via the first sub-network 1, the second bridge 129  
and the second sub-network 2. This data connection is of a asynchronous tran-  
5 sient connection type. In the following, for such a data connection reference is  
only made to "third control connection 2001".

Further, Fig. 5a shows an arrow 2002 which is arranged between the Memory  
Stick Walkman 105 and the PC 101. This arrow 2002 defines a bidirectional  
10 data connection between the Memory Stick Walkman 105 and the PC 101 which  
is used to control the Memory Stick Walkman 105 and is realized via the first  
sub-network 1. In the following, for such a data connection reference is only  
made to "fourth control connection 2002". Like the third control connection  
2001, the fourth control connection 2002 is also of a asynchronous transient  
15 connection type.

Still further, Fig. 5a shows an arrow 2003 which is arranged between the DAB-  
Tuner 108 and the Memory Stick Walkman 105. Said arrow 2003 defines a uni-  
directional isochronous data connection between the DAB-Tuner 108 and the  
20 Memory Stick Walkman 105, which is realized via the first sub-network 1, the  
second bridge 129 and the second sub-network 2. Data streams can be trans-  
ferred by this data connection. In the following, such data connection is only re-  
ferred to "third transfer connection 2003". It is to be noted that the third data  
connection is logically different from the third and fourth control connections  
25 2001 and 2002 which are used to negotiate or to set up the third transfer con-  
nection 2003 as will be explained further below.

In the following, the necessary steps for copying the DAB audio stream from  
the DAB-Tuner 108 to the Memory Stick Walkman 105 are explained with  
30 reference to Fig. 5b. In a first step S 501, the user switches on the DAB-Tuner  
108. In return, in step S 502, the DAB-Tuner 108 announces to the PC 101 via  
the third control connection 2001 to be on the bus, whereinafter the MMI  
implemented in the PC 101 displays the present new bus topology to the user in  
step S 503. In step S 504, the user switches on the Memory Stick Walkman 105,  
35 wherein in step S 505, the Memory Stick Walkman 105 announces to the PC  
101 to be on the bus via the fourth control connection 2002. After this change  
of the bus topology, in step S 506, the MMI displays the present new bus

1 topology to the user.

As soon as the user has taken said preparatory steps, in step S 507, he selects the icon assigned to the Memory Stick Walkman 105, which makes the PC 101  
5 sending a control signal in step S 508 via the fourth connection 2002 in order to read the directory of the Memory Stick Walkman 105. In return, in step S 509, respective information of the directory data of the Memory Stick Walkman 105 is sent back to the PC 101 via the fourth control connection 2002. Subsequently, in step S 510, the present directory of the Memory Stick Walkman 105 is  
10 displayed to the user via the MMI.

In step S 511, the user selects the icon assigned to the DAB-Tuner 108 which is displayed on the MMI, in order to make the PC 101 to send a control signal in  
15 step S 512 to the DAB-Tuner 108 via the third control connection 2001 in order to read its status/property data. As for result, respective information of the status/property data of the DAB-Tuner 108 are sent back to the PC 101 via the third control connection 2001 in step S 513, which makes the MMI to display the present available DAB services to the user in step S 514.

20 Subsequently in step S 515, the user drags a DAB audio stream and drops it on an icon assigned to a directory of the Memory Stick Walkman 105. Following this operation, in step S 516, the PC 101 sends a control signal to the Memory Stick Walkman 105 via the fourth control connection 2002, in order to setup the Memory Stick Walkman 105 for receiving data and writing to a file. In step S  
25 517, the PC 101 sends a control signal to the DAB-Tuner 108 via the third control connection 2001, in order to setup the DAB-Tuner 108 for sending data to the Memory Stick Walkman 105. Finally, as for result, the DAB-Tuner 108 copies said DAB audio stream to the Memory Stick Walkman 105 via the third transfer connection 2003, wherein the copying of said data stream is accom-  
30 plished.

With respect to the examples of transferring a data stream explained above with reference to Figs. 4 and 5, it is to be understood that it might be further possible to monitor the status of said stream transfer via the MMI of the PC 101. In  
35 such a case the necessary data information would be transferred to the PC 101 through an unidirectional isochronous data connection between the respective device, e.g. the DVHS 106 or the DAB-Tuner 108, respectively, and the PC 101.



10 It is to be understood that the invention is not limited to the examples explained with reference to the Figs. 1 to 5. Of course, any other operation between devices and/or services included within said home network may also be executed according to the present invention.

20

25

30

35